



4+1-Port USB 2.0 PCI Card



Model Number: UP04V3

General Descriptions

UP04V3 is a 4+1-Port USB 2.0 PCI Card with 4+1 USB 2.0 ports (Type A connector) and maximum data transfer rate up to 480 Mbps. UP04V3 uses advanced VIA USB 2.0 Controller solution with complete set of industry standard features for high-speed data transfer.

This product is made in ISO9001 approved factory. UP04V3 4+1-Port USB 2.0 PCI Card complies with FCC part15 regulations and CE approval.

Features and Benefits

- Compliant with USB specification Rev. 2.0 and USB power management requirements
- Compliant with Enhanced Host Controller Interface Specification Rev. 0.95
- Compliant with Universal Host Controller Interface Specification Rev. 1.1
- Plug and play compatible for easy installation and configuration
- Supports Bus-powered or self-powered capability with the suspend mode
- Supports PCI-Bus Power Management Interface Specification 1.1
- USB Hub supports high-speed (480 Mbps), full-speed (12 Mbps), and low-speed (1.5 Mbps) devices
- Supports individual or global overcurrent protection support

Specifications

Data Connection	Compliant with USB Specification Rev. 2.0 and maximum data transfer rate up to 480 Mbits/s USB ports support high-speed (480 Mbps), full-speed (12 Mbps), and low-speed (1.5 Mbps) devices
Interface	PCI Interface Four USB type A connectors
Power Consumption	5W Max, @2A
Operating Temperature	0° C ~ 45° C
Humidity	5 % ~ 95 % (non-condensing)
Storage Temperature	0° C ~ 70° C
Supported OS	Windows 98SE, ME, 2000 and XP
Minimum System Requirements	Pentium compatible processor 200 MHz and above Minimum 32 MB RAM Minimum 30 MB available hard disk space CD-ROM drive Available PCI slot
Regulations	FCC part 15, CE

V.1.0